



1. Material :
 Contae is: Phosphore Bronze
 insulater: PBT+30%
 G. F. UL 94V-0
 Shell: SPCC
2. Mechanical :
 Mating: 35N max.
 Withdrowa Force: 10N min.
 Darabirity: 1500 cycles min.
3. Elecetical :
 Current-max (amps) 1.5A
 Voitage-max (volts) 30V
 Withstanding Voltage 750V AC
 Contact Resistance (ohms) 30 milliohms max
 insulation Resistance (ohms) 1000 Megogms min.
4. Plating :
 Contacts: Gold And Tin Over
 Nickel Ploled
 Shell: Nickel over all plating.
5. Environmental :
 temperature Range: -55 to 85 .

产品图 MANUFACTURE DWG	公差一览表 TOLERANCE UNLESS OTHERWISE			Shenzhen City Xiangyunfeiwu Technology Co., Ltd			
	单位 UNITS	MM		INCH	产品名称		
.X	±0.20	.X	±----	角法 VIEW		制图 DRAWING	审核 CHKD
.XX	±0.10	.XX	±----	比例 SCALE	1:1	设计 DESIGN	核准 APPD
.XXX	±0.05	.XXX	±----	2013.08.29		版本 A1	图号 CKC1
				张数 1/1			